





DESCRIPTION

HZ-801A Mobile Phone 3G / 4G / 5G / LTE / GSM / CDMA / WiFi / Jammer 8 Bands 40W Output Power

SPECIFICATION

2G	GSM 850/900/1800/1900 (GPRS, EDGE)	1. The blocking effect will be limited to the room in which the device is installed. Best performance when the room is closed.
3G	CDMA 2000	
	B1 (2100 Mhz)	
	B8 (900 Mhz)	· ·
	900/2100 MHz UMTS, DC-HSPA+	2. It is environment friendly as the electromagnetic field
	HSDPA 800 / 850 / 900 / 1700 (AWS) / 1900 / 2100	strength is very low and it doesn't hurt human body.
4G	1, 2, 3, 4, 5, 6, 7, 8, 9, 11, 12, 13, 14, 17, 18, 19, 20, 21,	3. It is easy to use as it operates automatically when plugged in.
	25, 26, 28, 29, 30, 32, 34, 38, 39, 40, 41, 42, 46, 48, 66, 71	
	FD-LTE: 1800 MHz	
	TD-LTE: 2300 MHz	4. Unique dual fan ventilation and heat dissipation design to ensure continuous and stable operation for a long time.
	TD-LTE: 2600 MHz	
	FD-LTE: 2100/1800 MHz LTE, LTE-A	
	B3 (1800+) LTE	5. Power 40W, effective shielding distance radius (0-30m) shield distance depends on the strength of the environ- ment signal.
	B12 (700 MHz)	
	B38 (TD2600)	
	B40 (2300 MHz)	
5G	n78 (3500 Mhz), n40 (2300 Mhz), n41(2500 MHz)	6. It blocks all the frequencies of mobile phones 3G, 4G, 5G,
	1, 2, 3, 5, 28, 38, 41, 66, 71, 77, 78, 79, 260, 261	LTE, GSM, CDMA and Wifi signals with reference to the
	NB-IOT (LTE Cat-NB1)	frequencies mentioned in the table for Saudi Arabia.
WiFi	2400-2484 MHz	





©2023 CABCOMM System. All rights reserved. All trademarks identified by [®] or [™] are registered trademarks, respectively, of CABBCOMM. All specifications are subject to change without notice. Page-1 CS-130-1





Option: Effective shielding band: CDMA handset: 869-880 MHz,GSM mobile phone: 925-960MHz, DCS/PHS/4G: 1805-1920MHZ (including mobile 4G), Unicom, Telecom 3G mobile phone: 2110-2145 MHZ,Mobile 3G mobile phone: 2010-2025MHz,4G: 2300-2390Mhz, 4G: 2555-2655MHZ, 5G: 2500-3500MHZ, WIFI: 2400-2484MHZ, Other corresponding frequency bands can be added according to customer requirements.

Power supply	AC100-240V 50/60Hz
Jamming Range	Radius (0~10m) shield distance depends on the strength of the environment signal
Weight	1.8kg
Dimension	38*25.7*7cm
Working time	Without the time limit, May continue to work,
Antenna	200 mm Long
Warranty	1 year





© 2023 CABCOMM System. All rights reserved. All trademarks identified by [®] or [™] are registered trademarks, respectively, of CABBCOMM. All specifications are subject to change without notice. Page-2 CS-130-1