



OPTICAL FIBER PIGTAIL (SINGLE/MULTI MODE)

The pigtails provide 900µm buffered fiber for ease of handling in fiber management such as panels, splice cassettes and wall boxes. The pigtails are terminated with physical contact (single mode & multimode) and angled physical contact (single mode) zirconia ferrule connectors which are manufactured with precision factory mounting and polishing techniques which helps assure high transmission quality

SPECIFICATIONS

Standards	IEC, EIA/TIA, Telcordia GR-326 Standards
Strength Member	Aramid Yarn
Cable Diameter	0.9mm / 2mm / 3mm
Fiber Type	OS2, OM3, OM4 , OM5
Jacket Material	LSZH
Insertion loss	≤ 0.3dB
Return loss	≥ 55 dB
Minimum Bend Radius Install	3.0cm
Long Term Bend Radius	2.0cm
Operating Temperature	-40°C to +85°C
Storage Temperature	-50°C to +85°C
Cable Color	Aqua , Purple, Yellow or 12 X Colours
Connector Type	SC, FC, ST, LC
Length	1m / 2m / 3m
Performance	Factory Tested
Compliant	RoHS & ISO
Application	1G -40G Applications

ORDER INFORMATION

Part Number	Description
FOSXXYY-TY	CABCOMM Fiber Optic Pigtail YY - XX TY - LSZH